CLAIMS

What is claimed is:

1.   A method of handling memory errors comprising:

       receiving a memory fault indication that is true if an error in the memory is
detected while executing a memory load request to retrieve a value
from the memory;

       receiving a speculative load indication that is true if the memory load
request was issued speculatively; and

       if the memory fault indication is true and the speculative load indication is
true,

       providing an error indication that the returned value is invalid,

       otherwise,

       performing error recovery.

2.   The method of claim 1, wherein the error indication is a flag bit associated
with the returned value.

3.   The method of claim 1, wherein the error indication is setting the returned
value to an invalid value.

4.   The method of claim 1, further comprising receiving a fault deferral
indication that is true if faults can be deferred, wherein providing an error
indication is performed if, in addition to the memory fault indication being
true and the speculative load indication being true, the fault deferral
indication is true.

5.   The method of claim 1, wherein providing an error indication is performed if,
in addition to the memory fault indication being true and the speculative
load indication being true, the error in the memory is uncorrectable.

6. A machine-readable medium that provides instructions, which when executed by a machine, cause the machine to perform operations comprising:

receiving a memory fault indication that is true if an error in the memory is detected while executing a memory load request to retrieve a value from the memory;

receiving a speculative load indication that is true if the memory load request was issued speculatively; and

if the memory fault indication is true and the speculative load indication is true,

providing an error indication that the returned value is invalid,

otherwise,

performing error recovery.

7. The machine-readable medium of claim 6, wherein the error indication is a flag bit associated with the returned value.

8. The machine-readable medium of claim 6, wherein the error indication is setting the returned value to an invalid value.

9. The machine-readable medium of claim 6, further comprising receiving a fault deferral indication that is true if faults can be deferred, wherein providing an error indication is performed if, in addition to the memory fault indication being true and the speculative load indication being true, the fault deferral indication is true.

10. The machine-readable medium of claim 6, wherein providing an error indication is performed if, in addition to the memory fault indication being true and the speculative load indication being true, the error in the memory is uncorrectable.

9

11. A machine comprising:

an interface to receive a value from a memory coupled to the machine;

a memory fault indicator that is true if an error in the memory is detected
while executing a memory load request to retrieve a value from the
memory;

a speculative load indicator that is true if the memory load request was
issued speculatively; and

a machine-readable medium that provides instructions, which when
executed by a machine, cause the machine to perform operations
including
if the memory fault indicator is true and the speculative load indicator
is true,
providing an error indication that the returned value is invalid,
otherwise,
performing error recovery.

12. The machine of claim 11, wherein the machine further comprises a register
to receive the value, and a flag bit associated with the register, wherein the
error indication is a defined value of the flag bit.

13. The machine of claim 11, wherein the machine further comprises a register
to receive the value, and the error indication is an invalid value in the
register.

14. The machine of claim 11, further comprising receiving a fault deferral
indicator from the machine to indicate that faults can be deferred, wherein
providing an error indication is performed if, in addition to the memory fault
indicator being true and the speculative load indicator being true, the fault
deferral indicator is true.

15. The machine of claim 11, wherein providing an error indication is performed if, in addition to the memory fault indication being true and the speculative load indication being true, the error in the memory is uncorrectable.

16. A system comprising:

a machine;

a memory coupled to the machine; and

a machine-readable medium that provides instructions, which when

executed by the machine, cause the machine to perform operations

including

receiving a memory fault indication that is true if an error in the

memory is detected while executing a memory load request to

retrieve a value from the memory,

receiving a speculative load indication that is true if the memory load

request was issued speculatively, and

if the memory fault indication is true and the speculative load

indication is true,

providing an error indication that the returned value is invalid,

otherwise,

performing error recovery.

17. The system of claim 16, wherein the machine further comprises a register to receive the value, and a flag bit associated with the register, wherein the error indication is a defined value of the flag bit.

18. The system of claim 16, wherein the machine further comprises a register to receive the value, and the error indication is an invalid value in the register.

19. The system of claim 16, further comprising receiving a fault deferral indicator from the machine to indicate that faults can be deferred, wherein providing an error indication is performed if, in addition to the memory fault

11

4   indicator being true and the speculative load indicator being true, the fault

5   deferral indicator is true.

1   20.   The system of claim 16, wherein providing an error indication is performed

2   if, in addition to the memory fault indication being true and the speculative

3   load indication being true, the error in the memory is uncorrectable.